

◇ 9T00-SWBX ON OMO





Q. TY: _____

SPEC.		TEST PRESS.	
FLUID		SHELL	HYDRO 3.5 MPa
PRESS.	MAX MPa	SEAT	AIR 0.6 MPa
TEMP.	MAX ℃	AIR	MPa

PIPE THREADS CONFORM WITH "JIS B 0203"
*MODIFIED P.T.F.E.

15	LOOSE STOPPER	1	SUS 304CSP	
14	RUBBER PACKING	1	SYNTHETIC RUBBER (HNBR)	
13	RATCHET NUT	1	SCS 13	
12	HEXAGON NUT	1	SUS 304	
11	SPRING WASHER	1	SUS 304	
10	HANDLE	1	SUS 304	
9	THRUST BEARING	1	P.T.F.E.	
8	THRUST PACKING	1	P.T.F.E.	
7	GASKET PACKING	1	P.T.F.E.	CARBON FILLED
6	BALL SEAT	2	P.T.F.E.	CARBON FILLED
5	GLAND	1	SUS 316	
4	STEM	1	SUS 316	*
3	BALL DISC	1	SCS 13A	
2	BODY CAP	1	SCS 13	
1	BODY	1	SCS 13	

No.	NAME OF PARTS	Q.TY	MATERIALS	REMARKS
NAME NICE JOINT AND SCREWED ENDS MINI BALL VALVES				
TYPE NJX-611		SIZE 20Sux3/4B		
DNG.No. XBAMS-0016◇		DATE MAR. 14. 2023.		
THIRD ANGLE PROJECTION METHOD		SCALE :		
APPROVED	CHECKED	DESIGNED	DRAWN	

O. N. INDUSTRIES LTD.

△		
△		
△		